## AgrimagP2

### **Applications**

Plastic flowmeter with power supply, datalogger, analogue and digital output for multiple applications.

- Industrial wastewater discharge
- Water Recycling Systems
- Irrigation
- Water Well Pump Stations
- Construction
- Grey water

#### **Advantages**

AgrimagP2 is a user friendly low cost flowmeter.

Digital datalogger - up to 131072 records.

4-20mA loop for easy connection with your current system.

Modbus RTU for easy SCADA connection.

Rigid polypropylene casing powered by external power supply.

Compatible with fitting kits for DIN, BSP, NPT and other common connections.

Accuracy rating of 1%.

- **1** 4-20mA loop and Modbus RTU
- Internal Datalogger
- External power supply
- No earthing rings required

#### **Features**

- 🐌 Sizes available: 25, 50, 80 mm
- 4 stainless steel electrodes
- Accuracy: ±1% from 10 % to 100 % of full scale range
- Power supply range is 9-35VDC
- Analogue output 4-20mA curent loop
- RS485 Modbus RTU

### AgrimagP2 technical specifications

Measurable media	Conductive fluids
Min. Media electrical conductivity	≥20µS/cm
Flow range	0.1 to 10 m/s
Displayed values	LCD display 128x64 PX graphical, Flow range (m3/h, l/s, l/m, US gal/min, UK gal/min), Volume (m3, l, US Gal, UK Gal), Total, Batch volume
Accuracy	±1% of reading from 100% to 10% of full scale ±3% of reading from 10% of full scale to cut-off
Full scale	1": 0.5 – 4.8 l/s 2": 1.9 – 18.9 l/s 3": 5.0 – 49.0 l/s
Power supply	9-35VDC Power supply available in special connector
Flow direction	Bi-directional measurement
Ambient temperature	-12 to 50°C (10 to 130°F)
Media temperature	0 to 60°C (32 to 140°F)
Working pressure	150psi or 10.3 bars
Body material	Glass filled polypropylene
Connections	Flange clamps
Electrodes	4x stainless steel electrodes
Display	LCD 128 x 64 PX graphical, sleep mode
Control	3 touch buttons
Low flow cut-off	2% of full scale
Electronics protection	Nema 4X standard
Other features	Test of excitation coils, Earthing through 3rd and 4th electrodes, Empty pipe detection
Excitation frequency	1/1.67s
Samples per Average	4 excitations
Coils resistance	100Ω
Current loop output	Max. current 24mA
Digital Communication	RS485 communication bus + I/O
Digital Data logger	Flash memory 131 072 records, 15 seconds minimal record interval. Saves Date, Time and Total volume



### Agrimag connections and accessories\_\_\_\_\_

### \_ AgrimagP2

**MANIFOLD x MALE BSP** 

Avalliable for sizes:	Description	Part number
25mm MAN	1" Manifold x 1" Male BSP	M100BSP
50mm MAN	2" Manifold x 2" Male BSP	M220BSP
80mm MAN	3" Manifold x 3" Male BSP	M300BSP

### **MANIFOLD x FEMALE NPT THREAD**

Avalliable for sizes:	Description	Part number	
25mm MAN	1" Manifold x 1/2" Female NPT	M100050FPT	
25mm MAN	1" Manifold x 3/4" Female NPT	M100075FPT	
25mm MAN	1" Manifold x 1" Female NPT	M100FPT	
50mm MAN	2" Manifold x 2" Female NPT	M220FPT	
80mm MAN	3" Manifold x 3" Female NPT	M300FPT	

I	MANIFOLD x NPT THRE	AD
Avalliable for sizes:	Description	Part number
25mm MAN	1" Manifold x 3/4" Male NPT	M100075MPT
25mm MAN	1" Manifold x 1.1/4" Male NPT	M100125MPT
25mm MAN	1" Manifold x 1" Male NPT	M100MPT
50mm MAN	2" Manifold x 2" Male NPT	M220MPT
80mm MAN	3" Manifold x 3" Male NPT	M300MPT

MANIFO	LD x MALE NPT THREA	D – 316SS
Avalliable for sizes:	Description	Part number
25mm MAN	1" Manifold x 3/4" Male NPT	M100MPTSS
25mm MAN	1" Manifold x 1.1/4" Male NPT	M220150MPTSS
25mm MAN	1" Manifold x 1" Male NPT	M220MPTSS
50mm MAN	2" Manifold x 2" Male NPT	M300220MPTSS
80mm MAN	3" Manifold x 3" Male NPT	M300MPTSS

	MANIFOLD x MANIFOLI	D
Avalliable for sizes:	Description	Part number
25mm MAN	1" Manifold x 1 " Manifold	M100CPG
50mm MAN	2" Manifold x 2 " Manifold	M220CPG
50mm MAN	2" Manifold x 2" Manifold x 6" long	M220CPG6
80mm MAN	3" Manifold x 3" Manifold x 4" long	M300CPG
80mm MAN	3" Manifold x 3" Manifold x 7" long	M300CPG7

MAN	IFOLD x FEMALE COUPIE	RQDC
Avalliable for sizes:	Description	Part number
50mm MAN	2" Manifold x 2" Female coupler QDC	M220D

# AgrimagP2

### **MANIFOLD X FEMALE QDC**

Avalliable for sizes:	Description	Part number
25mm MAN	1" Manifold x 1" Male QDC	M100A
50mm MAN	2" Manifold x 2" Male QDC	M220A
80mm MAN	3" Manifold x 3" Male QDC	M300A

### **MANIFOLD X HOSE BARB**

Avalliable for sizes:	Description	Part number
25mm MAN	1" Manifold x 3/4" Hose Barb	M100075BRB
25mm MAN	1" Manifold x 1" Hose Barb	M100BRB
25mm MAN	1" Manifold x 1.1/4" Hose Barb	M100125BRB
50mm MAN	2" Manifold x 1.1/4" Hose Barb	M220125BRB
50mm MAN	2" Manifold x 1.1/2" Hose Barb	M220150BRB
50mm MAN	2" Manifold x 2" Hose Barb	M220BRB
80mm MAN	3" Manifold x 2" Hose Barb	M300220BRB
80mm MAN	3" Manifold x 3" Hose Barb	M300BRB



	CLAMP	
Avalliable for sizes:	Description	Part number
25mm MAN	1" Clamp	FC100
50mm MAN	2" Clamp	FC220
80mm MAN	3" Clamp	FC300



	GASKET	
Avalliable for sizes:	Description	Part number
25mm MAN	1" Gasket EPDM	M101G
50mm MAN	2" Gasket EPDM	M221G
80mm MAN	3" Gasket EPDM	M301G

	GASKET VITON TYP	E
Avalliable for sizes:	Description	Part number
25mm MAN	1" Gasket Viton type	M100GV
50mm MAN	2" Gasket Viton type	200GV
80mm MAN	3" Gasket Viton type	300GV